

**PRODUCT BRAND:**

**ACTIV8** Friction Reducer

**SUPPLIED BY:**

AB Slotsport  
3 St James Terrace  
Riding Mill  
Northumberland NE44 6ED

**EMERGENCY**

**PHONE:** +44 (0) 1434682475

**INTENDED USE:**

**PRODUCT**

**COMPOSITION:**

As a lubrication additive  
Alkanes C14 - C17 Light Hydraulic oil Carrier 50/50

**HAZARD**

**IDENTIFICATION:**

Low Acute toxicity under normal conditions of handling and use.  
Slightly irritating to eyes. Repeated exposure to high levels may produce liver and kidney damage.

**EXPOSURE**

**ROUTE SYMPTOM TREATMENT**

**INHALATION** High concentrations may cause irritation.

Remove from exposure. Rest and in severe cases, or if recovery is not rapid, seek medical advice.

**SKIN CONTACT**

Prolonged or repeated exposure may result in slight irritation.

Drench skin with water. Remove contaminated clothing and wash before reuse. If irritation persists, seek medical attention.

**EYE CONTACT** Slight irritation. Irrigate thoroughly with water for at least 10 minutes. Obtain medical advice.

**INGESTION** Large doses may cause stomach upset.

Wash out mouth with water. Do not induce vomiting. If patient feels unwell, seek medical attention.

**FIRE FIGHTING**

**MEASURES:**

Use extinguisher suitable for fire conditions.  
Self contained breathing apparatus.

**HAZARDOUS**

**COMBUSTION**

**PRODUCTS:**

Hydrogen chloride may be evolved above 200° c.

**SPILLAGE**

**MEASURES -**

**Clean up procedure:**

Use sand, earth or other suitable absorbent material.  
Dispose of according to local. Regulations

**ENVIRONMENTAL**

**PRECAUTIONS:**

Do not allow material to enter drains, sewers or watercourses. Uncontrolled discharges must be reported to the appropriate regulatory body.

**HANDLING:** Avoid contact with eyes and prolonged skin contact. Store in original containers or lined mild steel tanks. Store below 40° c.

**PHYSICAL AND  
CHEMICAL  
PROPERTIES:**

**Appearance** Light straw **Freeze pour point** -10° c **Vapour density** Heavier than air

**Odour** Medium oil **Density @15°C** 1.07

**Boiling point** >200° c **Solubility in water** Insoluble

**DISPOSAL  
CONSIDERATIONS:**

**Substance:** Disposal via authorized waste disposal contractor to approved waste site.

**Container:** As above. Do not puncture or cut up until purged of product.

**TRANSPORT**

**INFORMATION:** This product is not regulated for road transport in the UK.

**OTHER  
INFORMATION:**

This material is usually used as an extreme pressure oil additive. The information contained in this data sheet does not constitute a complete assessment of workplace risks. The user must satisfy himself that the product is entirely suitable for his purpose.

**LEGAL**

**DISCLAIMER:**

The above information is based on the present state of our knowledge of the product at the time of publication. This information is given in good faith, no warranty is implied with respect to the quality or the specifications of the product. The user must satisfy himself that the product is entirely suitable for his use.